

# Longse



## SPECIFICATION

|                        |   |
|------------------------|---|
| Model NO.              | BMSDHTC500FPE-ECO   |
| Video Output Mode      | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps;CVBS |
| <b>Camera</b>          |   |
| Image Sensor           | 1/3.2" CMOS Sensor  |
| Image Resolution       | 5M:2592*1944 4M:2560*1440 2M:1920*1080  |
| TV System              | PAL/NTSC  |
| Electronic Shutter     | Auto  |
| Minimun Illumination   | Color : 0.03 lux@F2.0, AGC ON; B/W : 0 lux with IR  |
| Scanning System        | Progressive Scan  |
| <b>Lens</b>            |   |
| Focus Length           | 3.6mm   |
| Focus Control          | Fixed   |
| Lens Type              | Fixed   |
| <b>Night Vision</b>    |   |
| IR Cut Filter          | YES   |
| Infrared LED           | 42μ x 2PCS  |
| Light Distance         | 25M   |
| IR Status              | AGC auto control  |
| <b>Camera Features</b> |   |

|                 |                |
|-----------------|----------------|
| Starlight       | N/A            |
| Day/Night       | YES            |
| OSD Menu        | YES            |
| WDR             | DWDR           |
| UTC             | YES            |
| Noise Reduction | 2DNR           |
| Coaxial Audio   | YES(only TVI ) |
| White Balance   | AUTO / MANUAL  |
| Gain Control    | AUTO           |

General

|                       |   |
|-----------------------|---|
| Housing               | Front Cover: Metal Main body: Plastic, IP67 |
| Bracket               | YES   |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max                       |
| Storage Temperature   | -20℃ ~ +60℃ RH95% Max                       |
| Power Source          | DC12V±10%, 500mA                            |
| Dimension             | 176.6(W) x 67(H) x 70(D)mm                  |
| Weight                | 336g  |