Longse

## SPECIFICATION

| | |
|---|---|
| **Model NO.** | **LIRDCAHTC500FPE-ECO** |
| **Video Output Mode** | **AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps;CVBS** |
| **Camera** | |
| Image Sensor | 1/3.2" CMOS Sensor |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimun Illumination | Color : 0.03 lux@F2.0, AGC ON; B/W : 0 lux with IR |
| Scanning System | Progressive Scan |
| **Lens** | |
| Focus Length | 2.8-12mm |
| Focus Control | Manual |
| Lens Type | Varifocal |
| **Night Vision** | |
| IR Cut Filter | YES |
| Infrared LED | 14μ x 24PCS |
| Light Distance | 30M |
| IR Status | AGC auto control |
| **Camera Features** | |

Longse

| | |
|---|---|
| Starlight | N/A |
| Day/Night | YES |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | 2DNR |
| Coaxial Audio | YES(only TVI ) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |
| **General** | |
| Housing | Metal, IP67 |
| Bracket | Optional |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%, 750mA |
| Dimension | ∅119 x 98(H) mm |
| Weight | 800g |

Longse