



SPECIFICATION			
Model NO.	BMSDHTC500FKE	BMSDTHC500FKE	
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps,5M@20fps/12.5fps,4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps.4M/2M@30fps/25fps:CVBS		
Camera			
Image Sensor	1/2.5" CMOS sensor		
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080		
TV System	PAL/NTSC		
Electronic Shutter	Auto		
Minimun I <mark>llumin</mark> ation	Color: 0.03 lux@F2.0, AGC ON; B/W: 0 lux with IR		
Scanning Syst <mark>em</mark>	Progressive Scan		
Lens			
Focus Length	3.6mm		
Focus Control	Fixed		
Lens Type	Fixed		
Night Vision	•		
IR Cut Filter	YES		
Infrared LED	42μ x 2PCS		
	25M		
Infrared Distance		AGC Auto Control	

Starlight	N/A	
Day/Night	YES	
OSD Menu	YES	
WDR	DWDR	
итс	YES	
Noise Reduction	DNR	
Coaxial Audio	YES(only TVI )	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
General		
Housing	Front Cover: Metal ,Back Cover: Plastic, IP67	
Bracket	YES	
Operation Temperature	-10℃ ~+60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 450mA	
Dimension	176.6(W) x 67(H) x 70(D)mm	
Weight	336g	