Longse

SPECIFICATION

Model NO.	**NVR3009S1P4**
System	
Main Processor	ARM Cortex A7 Processor
Operating System	Embedded LINUX
Video	
Input	9CH(8MP/6MP/5MP/4MP/3MP/1080p/1280x1024/960p/720p/D1/CIF)
Output	1* HD
Audio	
Input	N/A
Output	N/A
Audio Bit Rate	64kbps
Audio Compression standard	G711U, G711A, MP2L2
Intercom	N/A
Alarm	
Sensor Input	N/A
Output	N/A
Motion Detection	9 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot and Screen Tips, Pop-up Window, Notify Surveillance Center
Display	
HD Output1	1920*1080/1280*1024/1280*720/1024*768
HD Output2	N/A
VGA	N/A
Display Split	9CH/8CH/6CH/4CH/2CH/1CH
Digital Zoom	YES
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm
Recording	
Video Compression	H265/H264/H265+/H264+
Resolution	4k(3840×2160),5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536),1080P(1920×1080),960P(1280x960),720P(1280×720),D1 (720×576/720×480)
Record Rate	PAL: 4K@8CHx25fps,5MP@9CH×25fps,4MP@9CHx25fps,3MP@9CH×25fps,1080P@9CH×25fps, 960P@9CH×25fps720P@9CH×25fps, D1@9CH×25fps NTSC: 4K@8CHx30fps,5MP@9CH×30fps,4MP@9CH×30fps,3MP@9CH×30fps,1080P@9CH×30fps, 960P@9CH×30fps, 720P@9CH×30fps, D1@9CH×30fps
Record Mode	Manual\Timer\Motion Detection\Smart Event
Playback & Backup	
Local Sync Playback	1CH 4K@30fps, 1CH 5MP@30fps,2CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@30fps,9CH 720P@30fps
Decode Capability	1080P(1920x1080)@120fps
Remote Sync Playback	YES
Search Mode	ALL, Timing Video, Motion Detection, Tag search,Smart Event,Pictrue,Log

Longse

Playback Functions	Play, pause, fast forward, rewind, previous frame, next frame, electronic zoom, clip, audio
Backup Mode	USB Device/Network
Network	
Interface	1xRJ45 (10M/100M self-Adaptive Ethernet Interface)
Incoming Bandwidth	72Mbps
Outgoing Bandwidth	48Mbps
Network Functions	IPv6/TCP/IP, HTTP,HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, p2p,PPPOE
Onvif	Profile S, Profile T
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10/Windows 11/MAC OS
Cloud Support	Yes
Smart Phone	iPhone, Android
POE	4x Independent 100Mbps POE Network Interfaces(Output power AT mode 30W per port), 45/78 line order, Total Power Output≤ 45W, Support Plug and Play, Support network cable extended mode Max. 200M
WIFI	N/A
Storage	
Interface Type	1 SATA Hard Disk Interface (3.5" SATA)
Capacity	Up to 8TB capacity
eSATA	N/A
General	
Language UI	Simplified Chinese, Traditional Chinese, English, Polski, Czech, Arabic, German, French, Portuguese, Spanish, Italian, Hungarian, Korean, Dutch, Greek, Janpanese, Ukrainian, Kazakh
USB Interface	2 USB 2.0 Interfaces
RS485	N/A
Power consumption	DC48V/1.36A ≤ 6W (Without Hard Disk and POE)
Working Environment	-10℃～50℃, 10%～90%(humidity)
Product Dimension(W×D×H)	200 x 175 x 40mm
Net Weight	1.5kg(without HDD)
Gross Weight	N/A

Lonose